

Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

## Not for sale in the USA

## Section 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### 1.1 Product identifier

Trade name

SolidARC 105 MSM S6; SolidARC 110 MSM S6; SolidARC 115 MSM S6.

Article-Nº

Product/Article	Diameter (Inch)	Packaging (Lbs)	Part Number
SolidARC 105 MSM S6	0.035	44	11265033
SolidARC 105 MSM S6	0.045	44	11265451
SolidARC 105 MSM S6	0.035	550	11279002
SolidARC 105 MSM S6	0.045	550	11279003
SolidARC 115 MSM S6	0.035	44	11023693
SolidARC 115 MSM S6	0.045	44	11023697
SolidARC 105 MSM S6	0.025	11	11199854
SolidARC 105 MSM S6	0.030	11	11199855
SolidARC 105 MSM S6	0.035	11	11199856
SolidARC 110 MSM S6	0.035	44	11199568
SolidARC 110 MSM S6	0.045	44	11199852
SolidARC 110 MSM S6	0.035	500	11201275
SolidARC 110 MSM S6	0.045	500	11201276

1.2 Relevant identified uses of the substance or mixture and uses advised against

Article type GMAW/GTAW Un-alloyed steel wire electrodes & Rods Classification: AWS SFA 5.18

Use Gas shielded Arc welding

1.3 Details of the supplier of the safety data sheet

Supplier Messer Canada Inc.

Street address 5860 Chedworth Way, Mississauga

Ontario L5R 0A2

Canada

Telephone 1-866-385-5349

Fax **905-501-1717** 

Email info@messer-ca.com

1.4 Emergency telephone number

Available outside office hours Yes

**Emergency phone number** (24 Hour): (905) 501-0802 or CHEMTREC (800) 424-9300



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

Other:

Additional product information Web site: www.messer-ca.com

## **Section 2. HAZARDS IDENTIFICATION**

## 2.1 Classification of the substance or mixture

Classification according to applicable national regulations.

2.2 Label elements

Refer to label.

### 2.3 Other hazards

When the product is used in the welding process the most important hazards are:

Overexposure to fumes and gases from welding can be dangerous to health.

Watch out for splatter, hot metal and slag. It may cause skin burn and cause fire.

Arc rays can injure eyes and burn skin. Electric shock can kill. Avoid touching live electrical parts.

## Section 3. COMPOSITION / INFORMATION ON INGREDIENTS

### 3.1 Substances

This product is a mixture and please refer to Section 3.2

3.2 Mixtures								
AWS Clas's	Fe %	C %	Mn %	Si %	Cu¹ %	Ti %	Zr %	AI %
CAS Number	7439-89-6	7440- 44-0	7439-96-5	7440-21-3	7440-50-8	7440- 32-6	7440- 67-7	7429-90-5
ER70S-6	>96	0.07 to 0.15	1.40 to 1.85	0.80 to 1.15	<0.5	N/Av	N/Av	N/Av
LD <sub>50</sub> (specie,route)	30 g/kg (rat,oral)	N/Av	9 g/kg (rat,oral)	3160 mg/kg (rat,oral)	9g/kg (mouse, oral)	N/Av	N/Av	N/Av
LC <sub>50</sub> (specie)	N/Av	N/Av	N/Av	N/Av	N/Av	N/Av	N/Av	N/Av

## **Section 4. FIRST AND MEASURES**

4.1 Description of first aid measures

**Inhalation** IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position

comfortable for breathing. Call a physician if symptoms occur.

Skin contact

Burns should be treated by a doctor.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Burns from radiation, see doctor.

**Ingestion** Contact a doctor if more than an insignificant amount has been swallowed.

2



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

4.2 Most important symptoms and effects, both acute and delayed

Inhalation Inhalation of vapours may cause irritation of the respiratory system in very susceptible

persons.

4.3 Indication of any immediate medical attention and special treatment needed

Not available

### Section 5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2), powder or diffuse jet of water. In case of major fire: Extinguish fire

with diffuse jet of water or foam.

5.2 Special hazards arising from the substance or mixture

Not available

5.3 Advice for fire fighters

Special protective equipment for fire fighters

No specific measures required for these electrodes prior to gouging.

Gouging should not be carried out in the presence of flammable materials, vapours, tanks, cisterns and pipes and other containers which have held flammable substances unless

these have been checked and certified safe.

During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.

## Section 6. ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures

General ventilation and local fume extraction must be adequate to keep fume concentrations within safe limits. Use respiratory equipment when welding in a confined space. Wear protective clothing and eye protection appropriate to arc welding. Skin contact should be avoided to prevent possible allergic reactions.

## 6.2 Environmental precautions

Try to prevent the material from entering drains or water courses.

6.3 Methods and material for containment and cleaning up

Not applicable

6.4 Reference to other sections

Personal protection: see section 8 and for disposal see section 13. Environmental precautions, paragraph 12. See also section 7 Precautions for safe handling.

### Section 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Preventive handling precautions

Ensure adequate ventilation for the welder and others. Use respiratory equipment when welding in a confined space. Wear protective clothing and eye protection appropriate to arc



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

welding. Remove all flammable materials and liquids before welding.

General hygiene Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Store welding consumables inside a room without humidity. Do not store welding consumables directly on the ground or beside walls. Store away from chemical substances like acids which could cause chemical reactions.

7.3 Specific end use(s) Welding process.

## Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

Welding fume component	CAS №.	TLV-TWA	TLV-STEL	Other
Iron oxide fume (as Fe)	1309-37-1	5mg/m <sup>3</sup> Respirable particulate mass	N/Av	N/Av
Manganese and its inorganic compounds (as Mn)	7439-96-5 and others	0.2 mg/m <sup>3</sup>	N/Av	N/Av
Chromium VI compounds (as Cr)	1333-82-0	0.05mg/m <sup>3</sup>	N/Av	N/Av
Chromium III compounds (as Cr)	1308-38-9	0.5mg/m <sup>3</sup>	N/Av	N/Av
Nickel and its inorganic compounds Water soluble Water insoluble	7440-02-0	1.5 mg/m3 N/Av	N/Av N/Av	N/Av 1.0 mg/m3
Copper Fume	7440-50-8	0.2 mg/m³ (fume)	N/Av	0.1 mg/m3 (fume)
Nitrogen dioxide	10102-44-0	0.2ppm	N/Av	N/Av
Nitrogen monoxide	10102-43-9	25ppm	N/Av	N/Av
Ozone	10028-15-6	*	N/Av	N/Av
Carbon dioxide	124-38-9	5000ppm	30000ppm	5000ppm
Carbon monoxide	630-08-0	25ppm	N/Av	50ppm
Aluminium Inhalable Respirable dust	1344-28-1	1 mg/m <sup>3</sup> (respirable)	N/Av	N/Av
Zirconium compounds	7440-67-7	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	N/Av

### 8.2 Exposure controls

Environmental Exposure Controls - refer to Section 6 of this SDS

**Technical precaution measures**General ventilation and local fume extraction must be adequate to keep fume concentrations within safe limits.



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

Eye / face protection Wear eye protection appropriate for welding.

Safety gloves Skin contact should be avoided to prevent possible allergic reactions.

Other skin protection Wear body protection which helps to prevent injury from radiation, sparks and electric

Respiratory protection Use respiratory equipment when welding in a confined space. Wear protective clothing

and eye protection appropriate to arc welding.

## Section 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance, colour Generally grey or coppered coloured when coated

Appearance, physical state Metal wire or Rod **Auto-ignition temperature** Not applicable **Auto-flammability** Not auto-flammable **Decomposition temperature** Not applicable **Evaporation rate** Not applicable

**Explosive properties** Not explosive Flammability (solid gas) Not applicable

Flash point Not applicable

> **Form** Fast

Initial boiling point and boiling Not applicable range

Melting point / Freezing point Not available

> Odour Odourless

Odour threshold Not available Not available Oxidising properties

Partition coefficient: n-octanol / Not applicable

water

pH value Not applicable Relative density Not applicable Solubility Not available

Solubility in water Insoluble

Upper / lower flammability or explosive limits

Not applicable

Vapour density Not applicable Not applicable Vapour pressure

**Viscosity** Not applicable

9.2 Other information

Not applicable

Other

Density 7.98g/cm<sup>3</sup>

## Section 10. STABILITY AND REACTIVITY

10.1 Reactivity

Not available

10.2 Chemical stability

Stable under the recommended storage and handling conditions prescribed. Hazardous polymerization will not occur. Incompatible materials and conditions to avoid are usually



Version number: 1

**Replaces SDS: 2009-11-23** 

Issued: 2020-03-05

related to welding.

10.3 Possibility of hazardous reactions

Not applicable

10.4 Conditions to avoid

None under normal conditions

10.5 Incompatible materials

Not applicable



Version number: 1

**Replaces SDS: 2009-11-23** 

**Issued:** 2020-03-05

## 10.6 Hazardous decomposition products

Welding fumes and gases. Additional fume may arise from coatings and contaminants on the base material. Hazardous combustion products - Carbon oxides and other irritating/toxic fumes and smoke.

Welding fume component	CAS №.	Classification (67/548EEC) CLP (1272/2008)		Concentration of classified fume components	
Aluminium oxide (Al)	1344-28-1	-	-	-	<0.1
Barium (Ba)	7440-39-3	-	-	-	<0.1
Bismuth oxide (Bi)	12640-40-3	-	-	-	<0.1
Calcium (Ca)	1305-78-8	-	-	-	<0.1 to 0.2
Cobalt oxide (Co)	1307-96-6	R22: Harmful if swallowed R43: May cause sensitisation by contact	Acute tox 4 (oral)	H302	<0.1
		by contact	Skin sens. 1	H317	
		R45: May cause cancer	Carc. 1B	H350	<0.1
Chromium III compounds (as Cr)	24613-89-6	R35: Causes severe burns R43: May cause sensitisation	Skin Corr. 1A	H314	
compounds (as Ci)		by skin contact	Skin Sens. 1	H317	
Copper oxide (Cu)	1317-38-0	-	-	-	0.3 to 1.1
Iron oxide (Fe)	1332-37-2	-	-	-	45.8 to 61.4
Potassium (K)	7440-09-7	R34: Causes burns	Skin Corr. 1B	H314	<0.1
Lithium (Li)	7439-93-2	R34: Causes burns	Skin Corr. 1B	H314	<0.1
Magnesium oxide (Mg)	1309-48-4	-	-	-	<0.1
Manganese (Mn)	7439-96-5	-	-	-	6.3 to 15.0
Molybdenum (Mo)	7439-98-7	Molybdenum trioxide R36/37: Irritating to eyes and respiratory system R40: Limited evidence of carcinogenic effect	Molybdenum trioxide Carc. 2 Eye Irrit. 2 STOT SE 3	H351 H319 H335	<0.1
Sodium (Na)	7440-23-5	R34: Causes burns	Skin Corr. 1B	H314	<0.1
( 1)		R40: Limited evidence of	Carc. 2	H351	<0.1
Nickel (Ni)	7440-02-0	carcinogenic effect R43: May cause sensitisation by skin contact R48/23: Toxic danger of serious damage to health by prolonged exposure through inhalation R52/53: Harmful to aquatic	Skin sens 1 STOT RE 1	H317 H372	
		organisms, may cause long- term adverse effects in the aquatic environment			
Lead (Pb)	7439-92-1	-	-	-	<0.1
Silicon (Si)	7440-21-3	-	-	-	1.3 to 4.8
Titanium dioxide (Ti)	13463-67-7	-	-	-	<0.1
Vanadium (V)	7440-62-2	-	-	-	<0.1



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

Zinc (Zn)	7440-66-6	-	-	-	<0.1 to 0.7

Fume analysis: wt %			
ΑI	0.1 max		
Ca	0.1 to 0.2		
Fe	45.8 t0 61.4		
Mn	6.3 to 15		
s	1.3 to 4.8		
Zn	0.1 to 0.7		

### Section 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

Conditions to avoid: none in the form supplied

When welding, fumes and gases generated can be dangerous to health.

Acute toxiciy Excessive exposures may affect human health, as follows: Aspiration may cause pulmonary

oedema and pneumonitis Short-term overexposure can cause dizziness, nausea and irritation

of the nose, throat or eyes.

Irritation Not available

Corrosive effects Not available

Sensitisation May cause sensitisation by skin contact

Mutagenicity Not available

Carcinogenicity Welding fumes are possibly carcinogenic to humans

Repeated dose toxicity
Reproductive toxicity
Synergistic materials
Not available
Not available

## Section 12. ECOLOGICAL INFORMATION

## 12.1 Toxicity

The welding process can effect the environment if fume is released directly into the atmosphere. Residues from welding consumables could degrade and accumulate into soils and ground water.

12.2 Persistence and degradability

Not available

12.3 Bio accumulative potential

Not available

12.4 Mobility in Soil

Not available

12.5 Results of PBT and vPvB assessment



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

Not available

12.6 Other adverse effects

Not available

## Section 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

**Disposal considerations** Dispose of any product, residue or packing material according to national and local

regulations. Spent fume extraction filters shall be disposed of as dangerous waste.

Other

Naste Packaging and rod scrap should be disposed of as general waste or recycled. No special precautions are required for this product. Fume collected from extraction units should be

precautions are required for this product. Fume collected from extraction units should be disposed of in accordance with local regulations (including Provincial and Federal

Regulations). Collect all spillage.

## **Section 14. TRANSPORT INFORMATION**

14.1 UN number

Not applicable

14.2 UN proper shipping name

Not applicable

14.3 Transport hazard class(es)

Not applicable

14.4 Packing group

Not applicable

14.5 Environmental hazards

Not applicable

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to

Not applicable

Other



Version number: 1

Replaces SDS: 2009-11-23

**Issued:** 2020-03-05

**Dangerous goods** No special requirements are necessary in transporting these products.

Transportation of Dangerous Goods Regulations (TDGR):

TDG Classification: NOT REGULATED

Special case: N/Ap

## **Section 15. REGULATORY INFORMATION**

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture.

**EU regulations** Refer to national Regulations.

National regulations WHMIS Label Information: WARNING. Do not remove or cover this Warning. Protect yourself and

others. Read and understand this information. Electric shock can kill. Keep your head out of the fume. Arc rays and fume can affect others in your workplace. Comply with your employer's safety practices

and procedures: protect others.

Safety data sheet available on request from www.messer-ca.com.

WHMIS information: Product is regulated according to the Controlled Product Regulations (CPR) in Canada. This product has been classified in accordance with the hazard criteria of the Controlled

Products Regulations (CPR) and this SDS contains all the information required by the CPR.

WHMIS classification: D2A - Toxic Material with other effects.

15.2 Chemical safety assessment

Not available

## **Section 16. OTHER INFORMATION**

References to key literature and data sources

The customer should provide this Safety Data Sheet to any person involved in the materials use or further distribution. Messer Canada Inc. requests the users (or distributors) of this product to read this Safety Data Sheet carefully before usage.

Prepared by MESSER CANADA INC.

References

Safety Data Sheets from manufacturer/supplier.

Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2014.

Phrase meaning Abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstract Service

IARC International Agency for Research on Cancer

LC Lethal concentration LD Lethal Dosage N/Ap Not applicable N/Av Not available

NIOSH National Institute for Occupational Safety and Health

STEL Short-term Exposure Limit TLV Threshold Limit Value TWA Time Weighted Average

WHMIS Workplace Hazardous Materials Information System

Other

Manufacturer's notes

The information contained in this Safety Data Sheet relates only to the specific materials designated and may not be valid for such material used in combination with any other material or in any process.

Information is given in good faith and is based on the latest information available to Messer Canada and is, to the best of Messer Canada's knowledge and belief, accurate and reliable at the time of preparation. However, no representation, warranty or guarantee is made as to the accuracy, reliability or completeness of the information, and Messer Canada assumes no responsibility and disclaims any liability incurred in using this information.

The product is supplied on the condition that the user accepts the responsibility to satisfy himself as to



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

Read this Safety Data Sheet carefully and become aware of hazards implied and the safety information.

End of Document